

Prepared to U.S. OSHA, CMA, ANSI, Canadian WHMIS, Australian WorkSafe, Japanese Standard JIS Z 7250:2000, and EU REACH Regulations

## 1. PRODUCT AND COMPANY IDENTIFICATION

**Product Name:** **CARTRIDGES – SHOTSHELL**

**CAS Number:** Mixture – Metal Alloy

**Synonyms:** Shotgun Brands: Super-X, Supreme, Supreme High Velocity, Game Loads, Heavy Game Loads, Drylok Super Steel Non-Toxic, AA, AA International Target, AA Target, AA Traacker, AA Plus, AA Sporting Clays, AA Super Pigeon, Double X, Double X Magnum, Xpert, Upland, BRI, International Sporting, Ranger, Ranger Spreader, Ranger Low Recoil, Thunder Gold, Black Diamond, Super Dove, Super Lite, Super Speed, Super Speed Xtra, Super Sport, Rabbit and Squirrel, Dove and Quail, Duck and Pheasant, Pheasant, Super Pheasant, Blind Side, USA Brand, Super Target, Win3Gun, Rooster XR, Long Beard XR, Dual Bond, Partition Gold, XP3, Platinum Tip, Razorback XT, Rackmaster, Power Point, PDX1 Defender, Xtended Range, Target and Game, Xtra-Lite, Univeral, Fast Dove, Western, Winner, WinLite, Turkey, Hunter, White Wing, Grex, Shot-Lok.

Shotshell Payload Names: Lead Shot, Lead Slug, BRI Slug, Zinc Slug, Lead Buckshot, Steel Shot, Plated Steel Shot, Hex Steel Shot, XPert Steel, Saboted Slug, Bonded Dual Jacket Saboted Slug, BRI Rifled Slug, XP3, Platinum Tip, Razorback Slug, Rackmaster Slug, Power Point Slug, PDX1 Segmenting Slug, Grex buffer, Shot-Lok buffer, AA w ad, Drylok w ad, BRI sabot.

Shotshell Gauges: 410 Bore 2-1/2 inch, 410 Gauge 2-1/2 inch, 410 Bore 3 inch, 410 Gauge 3 inch, 28 Gauge 2-3/4 inch, 20 Gauge 2-3/4 inch, 20 Gauge 3 inch, 16 Gauge 2-3/4 inch, 12 Gauge 2-3/4 inch, 12 Gauge 3 inch, 12 Gauge 3-1/2 inch, 10 Gauge 3-1/2 inch.

Shotshell Proof Loads

**Product Use:** Shotgun Loaded Ammunition

**U.N. Number:** UN 0012

**U.N. Dangerous Goods Class** Explosive, 1.4S

**Manufacturer:** Olin Corporation – Winchester Division, Inc.

**Manufacturers' Address:** 600 Powder Mill Road, East Alton, IL 62024 [www.winchester.com](http://www.winchester.com)

**Emergency Telephone Number:** US/Canada: 1-800-424-9300  
Outside US/Canada: 703-527-3887

**SDS Control Group:** 618-258-3507 (Technical Information Only)

Olin SDS No.: 00068.0001

Issue Date: 6/1/15

Revision Date: 01/31/2017

Revision No.: 2

## 2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW: EXPLOSIVE. KEEP AWAY FROM HEAT. DO NOT SUBJECT TO MECHANICAL SHOCK. PARTICLES FROM FIRING MAY BE HARMFUL IF INHALED. DO NOT TAKE INTERNALLY.

## US DOT SYMBOLS



## CANADA (WHMIS) SYMBOLS

This Product is not subject to WHMIS

Class 6 Explosive

## GHS HAZARD SYMBOLS

**GHS Classifications:**

Explosive Division 1.4  
STOT RE Category 1  
Reproductive Toxicity Category 1A  
Aquatic Environment, Chronic II

**Signal Word:**

Danger

**Hazard Statements:**

H204: Fire or projection hazard  
H372: Causes damage to nervous system, kidney, and hematopoietic system through prolonged or repeated exposure  
H360: May damage fertility or the unborn child  
H411: Toxic to aquatic life with long lasting effects

**Target organs:**

Nervous, renal and hematopoietic systems

<b><u>Precautionary Statements:</u></b>	P102: Keep out of reach of children P210: Keep away from heat/sparks/open flame/hot surfaces P250: Do not subject to shock/friction P260: Do not breathe fumes P264: Wash hands thoroughly after handling P270: Do not eat, drink or smoke when using this product P271: Use only outdoors or in a well-ventilated area P273: Avoid release to the environment P280: Wear protective clothing/eye protection/hearing protection P370+P380: In case of fire: Evacuate area P374: Fight fire with normal precautions from a reasonable distance P410: Store in accordance with local regulations P501: Dispose of contents in accordance with local regulations
---	---

<b><u>GHS Pictograms:</u></b>	Explosive; Pictogram: exploding bomb Specific Target Organ Toxicity; Pictogram Code: GHS08 Environment; Pictogram Code: GHS09
-------------------------------	---

**EU Classifications:**

Hazard Symbols	E, T, N
Risk Phrases	R2: Risk of explosion by shock, friction, fire or other sources of ignition R48: Danger of serious damage to health by prolonged exposure R60: May impair fertility R63: Possible risk of harm to the unborn child R51/53: Toxic to aquatic organisms and may cause long-term adverse effects in the aquatic environment
Safety Phrases	S2: Keep out of reach of children S15: Keep away from heat S20/21: When using do not eat, drink or smoke S23: Do not breathe fumes S39: Wear eye/face protection S43: In case of fire, use Class A equipment S51: Use only in well-ventilated areas S61: Avoid release to the environment

**Health Hazards or Risks From Exposure**

This product is composed of a plastic tube and finished metal alloy cartridge which contains the various components completely sealed within. Therefore, under normal handling of this product, no exposure to any harmful materials will occur. When the ammunition is fired, a small amount of particles may be generated which may be slightly irritating to the eyes and the respiratory tract. The particles may contain trace amounts of these harmful substances:

**Lead:** Ingestion of large amounts of lead can cause abdominal pain, constipation, cramps, nausea and/or vomiting. Chronic exposure to lead can cause kidney damage, anemia, reproductive effects, developmental effects and permanent nervous system damage in humans including changes in cognitive function.

**Copper:** Inhalation of high concentrations of metallic copper dusts or fumes may cause nasal irritation and/or nausea, vomiting and stomach pain.

**Nitroglycerin:** Will produce dilation of blood vessels and drop in blood pressure which may affect the heart. It has also been shown to cause methemoglobinemia (cyanosis).

**Dibutyl phthalate:** May cause harm to the unborn child based on animal experiments. Possible risk of impaired fertility.

**Nickel:** Repeated exposure may cause an allergic skin reaction consisting of itching, redness, swelling, and rash or urticaria (hives) in sensitized individuals. Epidemiological studies in humans have shown an association between lung and nasal cancers and prolonged occupational exposures to high concentrations of nickel.

**Chromium:** Exposure to high concentrations of chromium dusts or fumes can cause severe respiratory and nasal irritation. Prolonged or repeated exposures to chromium dusts or fumes may cause perforation of the nasal septum, bloody nose and other symptoms of severe nasal irritation.

**Arsenic:** Epidemiological studies in humans have shown an association between increased incidences of lung and skin cancer and prolonged exposures to high concentrations of arsenic. Arsenic is classified as a known human carcinogen.

**Manganese:** Chronic exposure to very high concentrations of manganese dust has caused nervous system effects including muscle weakness, tremors, and behavioral changes.

It is unlikely that the amount of particles that someone would be exposed to from firing a loaded round would be sufficient to cause any of these effects.

**3. COMPOSITION / INFORMATION ON INGREDIENTS**

This MSDS covers a number of different products consisting of the following components:

- A) Load – can be Lead Shot or Slug, Steel Shot, or Bismuth Shot
- B) Plastic Shotshell Case
- C) Wad
- D) Propellant
- E) Primer
- F) Buffer (Considered to be a manufactured article)
- G) Resin

Components	% By Weight	CAS Number	EINECS/ ELINCS #
If The Load Is Lead Shot or Slug			
Lead	34 - 61	7439-92-1	231-100-4
Antimony	0.1 - 5	7440-36-0	231-146-5
Arsenic	0.1 – 1.5	7440-38-2	231-148-6
If The Load Is Steel Shot			
Iron	36 – 42	7439-89-6	231-096-4
Copper	0.1 – 4	7440-50-8	231-159-6
Manganese	0.1 – 3	7439-96-5	231-105-1
Nickel	0.1 – 3	7440-02-0	231-111-4
Chromium (non-hexavalent)	0.1 – 2	7440-47-3	231-157-5
Silicon	0.1 – 2	7440-21-3	231-130-8
If The Load Is Bismuth Shot			
Bismuth	18 -60	7440-69-9	231-177-4
Tin	0.8 – 6.2	7440-31-5	231-141-8
Zinc	5 – 15	7440-66-6	231-175-3
Ingredients In Other Components			
Polyethylene	10 – 17	9002-88-4	Polymer
Copper	7 – 12	7440-50-8	231-159-6
Zinc	1 – 4	7440-66-6	231-175-3
Wad(non-hazardous)	4 -11	Mixture	Not applicable
Nitrocellulose	5 - 10	9004-70-0	Polymer
Nitroglycerin	0.5 – 2	55-63-0	200-240-8
Dibutyl phthalate	0.5 – 2	84-74-2	201-55-74
Iron	1 -5	7439-89-6	231-096-4
Lead Styphnate	0.1 - 1	15245-44-0	239-290-0

#### 4. FIRST AID MEASURES

- Eye Contact:** Immediately flush out fume or particles with large amounts of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. If eye irritation develops, call a physician at once.
- Skin Contact:** Wash skin with plenty of soap and water.
- Inhalation:** If symptoms of lung irritation occur (coughing, wheezing or breathing difficulty), remove from exposure area to fresh air immediately. If breathing has stopped, perform artificial respiration. Keep affected person warm and at rest. Get medical attention.
- Ingestion:** If ingested, immediately call a physician.

#### Medical Conditions Aggravated By Exposure:

There are no medical conditions known to be aggravated by exposure to this product in its solid form. Exposure to lead can aggravate anemia, cardiovascular and respiratory disease.

#### Recommendations To Physicians:

Remove from exposure, if possible, and treat symptoms

#### 5. FIRE FIGHTING MEASURES

PROPERTY	VALUE	PROPERTY	VALUE
Explosive	Yes	Flammable	Not applicable
Combustible	Not applicable	Pyrophoric	No
Flash Point (°C):	Not applicable	Burning Rate of Material:	Not applicable
Lower Explosive Limit:	Not applicable	Autoignition Temp.:	No data

Upper Explosive Limit: | Not applicable |

Flammability Classification: (defined by 29 CFR 1910.1200) | Explosive

Unusual Fire and Explosion Hazards:  
Extinguishing Media:

Possible projection hazard.  
Flood area with water. If no water is available, carbon dioxide, dry chemical or earth may be used.

Special Firefighting Procedures:


Do not fight fire when fire reaches cargo. Cargo may explode.

Firefighters must wear self-contained breathing apparatus (SCBA) and full protective equipment. Structural firefighters' protective clothing will only provide limited protection.


Isolate materials not yet involved in the fire. Move containers from fire area if possible; otherwise, cool with carefully applied water spray.

Prevent runoff water from entering storm drains, bodies of water, or other environmentally sensitive areas, if practical.

**NFPA RATING SYSTEM**



**HMIS RATING SYSTEM**

HEALTH HAZARD (BLUE)		0*	
FLAMMABILITY HAZARD (RED)		1	
PHYSICAL HAZARD (YELLOW)		2	
PROTECTIVE EQUIPMENT			
EYES	PPE CODE	RESPIRATORY	HEARING
	A	See Sect 8	See Sect 8

**Hazard Scale:** 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe \* = Chronic hazard

## 6. ACCIDENTAL RELEASE MEASURES

**FOR ALL TRANSPORTATION ACCIDENTS, CALL CHEM TREC AT 800-424-9300.**

Spill Response:

A spill of this material will normally not require emergency response team capabilities. If, however, a large spill occurs, call 1-888-289-1911 for technical assistance.

Accidental Release Procedures:

Spills of this material should be handled carefully. Do not subject materials to mechanical shock. Collect material and place in a designated, labeled waste container. See Section 13 for waste disposal.

## 7. HANDLING AND STORAGE

Precautions for Safe Handling:

Use appropriate personal protective equipment (see Section 8). Workers should wash hands thoroughly after handling. Eating, drinking and smoking should be prohibited in areas where this material is handled and stored.

Conditions for Safe Storage:

Store in accordance with local regulations. Store in original containers in a cool, dry location away from Acids, Class A & B explosives, strong oxidizers, and caustics. Avoid mechanical impact or shock and electrical discharge.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters:

CAS #	CHEMICAL NAME	ACGIH TLV	OSHA PEL	INTERNATIONAL OELS
7440-50-8	Copper	0.2 mg/m <sup>3</sup> (fume), 1 mg/m <sup>3</sup> (dusts and mists)	0.1 mg/m <sup>3</sup> (fume) 1 mg/m <sup>3</sup> (dusts and mists)	Austria, Belgium, Canada: 0.2 mg/m <sup>3</sup> (fumes), 1 mg/m <sup>3</sup> (dusts) Denmark: 1.0 mg/m <sup>3</sup> (dust and powder) Germany (MAK): 0.1 mg/m <sup>3</sup> (fume), 1 mg/m <sup>3</sup> (dusts and mists)
7439-92-1	Lead	0.05 mg/m <sup>3</sup>	0.05 mg/m <sup>3</sup>	Austria, Denmark, Germany, Sweden, Switzerland: 0.1 mg/m <sup>3</sup> Norway, Poland: 0.05 mg/m <sup>3</sup>
7440-66-6	Zinc	None established	None established	None established
9004-70-0	Nitrocellulose	None established	None established	None established
55-63-0	Nitroglycerin	0.05 ppm (0.46 mg/m <sup>3</sup> ) Skin	Ceiling – 0.2 ppm (2 mg/m <sup>3</sup> )	Denmark: 0.02 ppm (0.2 mg/m <sup>3</sup> ) Norway, Sweden: 0.03 ppm (0.3 mg/m <sup>3</sup> ) Austria, Belgium, Germany, The Netherlands, Poland, Switzerland: 0.05 ppm (0.47 mg/m <sup>3</sup> ), skin Finland, France: 0.1 ppm (0.9 mg/m <sup>3</sup> ), skin U.K.: 0.2 ppm (2 mg/m <sup>3</sup> ), skin
84-74-2	Dibutyl phthalate	5 mg/m <sup>3</sup>	5 mg/m <sup>3</sup>	Belgium, Denmark, France, Netherlands, Switzerland, U.K.: 5 mg/m <sup>3</sup> Sweden: 3 mg/m <sup>3</sup>
7440-02-0	Nickel	1.5 mg/m <sup>3</sup> (inhalable)	1 mg/m <sup>3</sup>	Germany, MAK = 1 mg/m <sup>3</sup> Canada (B.C.), Czechoslovakia, Denmark, Norway – 0.05 mg/m <sup>3</sup> , K1, sensitizer Poland = 0.25 mg/m <sup>3</sup> Ireland, Sweden, Switzerland, U.K. = 0.5 mg/m <sup>3</sup> Belgium, Canada (Alberta & others), Finland, Japan, Mexico, Netherlands – 1 mg/m <sup>3</sup> Portugal = 1.5 mg/m <sup>3</sup>
7440-36-0	Antimony	0.5 mg/m <sup>3</sup>	0.5 mg/m <sup>3</sup>	Austria, Belgium, Denmark, France, Finland, Germany, Hungary, Netherlands, Norway, Poland, Sweden, UK: 0.5 mg/m <sup>3</sup>
7439-89-6	Iron	None established	None established	None established
7440-31-5	Tin	2 mg/m <sup>3</sup>	2 mg/m <sup>3</sup>	U.K. (LTEL): 5 mg/m <sup>3</sup> Austria & Germany (MAK), Belgium, Finland, Denmark, The Netherlands, Poland, Switzerland: 2 mg/m <sup>3</sup> Hungary, Norway: 1 mg/m <sup>3</sup>

7440-47-3	Chromium	0.5 mg/m <sup>3</sup>	1 mg/m <sup>3</sup>	Belgium, Denmark, France, Japan, Netherlands, Sweden, U.K. – 0.5 mg/m <sup>3</sup> Finland – 0.1 mg/m <sup>3</sup>
7440-38-8	Arsenic	0.01 mg/m <sup>3</sup>	0.01 mg/m <sup>3</sup>	Germany, MAK – 1 mg/m <sup>3</sup> Austria, Belgium, Finland, Japan, Holland, Czechoslovakia, Hungary and Poland - 0.5 mg/m <sup>3</sup> Italy – 0.25 mg/m <sup>3</sup> Switzerland, Canada (Alberta & others) – 0.2 mg/m <sup>3</sup> Sweden – 0.05 mg/m <sup>3</sup> Canada (B.C.), Denmark = 0.01 mg/m <sup>3</sup> , K1
7440-21-3	Silicon	None established	None established	Belgium, Denmark, France, Netherlands, U.K. – 10 mg/m <sup>3</sup> Switzerland – 4 mg/m <sup>3</sup>
7439-96-5	Manganese	0.2 mg/m <sup>3</sup>	Ceiling – 5 mg/m <sup>3</sup>	Belgium, Denmark, Finland, France, Switzerland, U.K. – 1 mg/m <sup>3</sup> Sweden – 2.5 mg/m <sup>3</sup> Germany (MAK) – 0.5 mg/m <sup>3</sup>
7440-69-9	Bismuth	None established	None established	None established
9002-88-4	Polyethylene	None established	None established	None established
55-63-0	Lead Styphnate	None established	None established	None established

<u>Engineering Controls:</u>	Local exhaust ventilation is recommended if significant dusting occurs or fumes are generated. Otherwise, use general exhaust ventilation.
<u>Respiratory Protection:</u>	Not normally needed. Maintain airborne contaminant concentrations below guidelines listed above. Use an appropriate approved air-purifying respirator equipped with HEPA cartridges/canisters where there is the potential for exceeding established occupational exposure limits.
<u>Eye/Face Protection:</u>	Use safety glasses.
<u>Hand Protection:</u>	Not normally needed.
<u>Skin Protection:</u>	Not normally needed.
<u>Hearing Protection:</u>	Not normally needed. During firing use hearing protection.
<u>General Hygiene:</u>	Do not eat, drink, or smoke while using this product. Wash hands thoroughly after use.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

PROPERTY	VALUE	PROPERTY	VALUE
<i>Appearance:</i>	Cylindrical plastic cartridge with metal base	<i>Physical State:</i>	Solid
<i>Odor:</i>	None	<i>Odor Threshold:</i>	None
<i>Boiling Point (°F):</i>	Not applicable	<i>Melting point:</i>	Not applicable
<i>Vapor Pressure (mm Hg):</i>	Not applicable	<i>Freezing point:</i>	Not applicable
<i>Vapor Density (air = 1):</i>	Not applicable	<i>Bulk Density:</i>	Not applicable
<i>Specific gravity (g/cc):</i>	Not applicable	<i>Viscosity (cps):</i>	Not applicable
<i>pH:</i>	Not applicable	<i>Decomposition Temperature:</i>	Not applicable
<i>Solubility in Water (20 °C):</i>	Insoluble	<i>Evaporation Rate:</i>	Not applicable
<i>Volatiles, Percent by volume:</i>	Not applicable	<i>Octanol/water partition coefficient:</i>	Not applicable

## 10. STABILITY AND REACTIVITY

<u>Stability:</u>	Stable under normal temperatures and pressure.
<u>Possibility of Hazardous Reactions:</u>	Hazardous polymerization will not occur
<u>Incompatible Materials:</u>	Acids, Class A & B explosives, strong oxidizers, and caustics
<u>Hazardous Decomposition Products:</u>	Nitrogen oxides, carbon monoxide, lead oxides, carbon dioxide, lead dust/fume
<u>Conditions to Avoid:</u>	Contact with incompatible materials. Physical damage to containers; cartridges may detonate if case is punctured.

## 11. TOXICOLOGICAL INFORMATION

Potential Routes of Entry: Inhalation, Skin, and by Ingestion.

The physical nature of this product makes absorption from any route unlikely. A small amount of inhalable particles may be created when cartridge is fired.

PRODUCT		SELECTED COMPONENTS									
		Lead	Nickel	Arsenic	Nitro-glycerin	Dibutyl phthalate	Copper	Manganese	Bismuth	Antimony	Chromium
Inhalation LC <sub>50</sub>	Particles generated from firing may be slightly toxic	No data	>12 mg/kg, it (rat)	No data	No data	4250 mg/m <sup>3</sup> (rat)	No data	No data	No data	No data	87 mg/m <sup>3</sup> (rat)
Skin Contact LD <sub>50</sub>	Skin absorption unlikely	No data	>7.5 g/kg, sc (rabbit)	No data	>280 mg/kg (rabbit)	>20 ml/kg (rabbit)	375 mg/kg, sc (rabbit)	No data	No data	No data	No data
Ingestion LD <sub>50</sub>	Ingestion unlikely	No data	>5 g/kg (rat)	763 mg/kg (rat)	105 mg/kg (rat)	8 g/kg (rat)	3.5 mg/kg, ip (mouse)	9 g/kg (rat)	5 g/kg (rat)	7 g/kg (rat)	27.5 mg/kg (rat)
Irritation	Particles generated from firing may be slightly irritating to the eyes	Not irritating	Respiratory irritant	No data	Mild eye & skin irritant	No data	Respiratory irritant	Mild eye & skin irritant	Not irritating	No data	Nasal & respiratory irritant
Sensitization	Sensitization to this Product has not been reported	No data	Skin sensitizer	No data	No data	No data	No data	No data	No data	No data	No data

Effects Of Acute Exposure:

Other Adverse Effects:

Target Organ Toxicity:

No reported target organ toxicity from this product. Lead has caused nervous system, kidney and hematopoietic system damage in humans and laboratory animals. Chronic exposure to very high concentrations of manganese dust has caused nervous system effects including muscle weakness, tremors, and behavioral changes in humans.

Reproductive Toxicity:

This product is not known or reported to cause reproductive effects. Lead has been shown to reduce male reproductive function in humans and laboratory animals. Dibutyl phthalate has caused adverse reproductive effects in animal studies. Exposure of male rats to high concentrations of nickel caused testicular degeneration.



<u>Teratogenicity (Birth Defects):</u>	This product is not known or reported to cause developmental toxicity. Lead has been shown to affect fetal development; changes including birth defects have been reported. Dibutyl phthalate has also been reported to cause adverse developmental effects in animal studies.
<u>Mutagenicity:</u>	This product is not known or reported to be mutagenic. Lead has been shown to be mutagenic in several <i>in vitro</i> assays. Nickel has been shown to be mutagenic in <i>in vitro</i> studies.
<u>Carcinogenicity:</u>	This product is not listed as a carcinogen by OSHA, NTP or IARC. IARC lists lead as possibly carcinogenic to humans, group 2B. Arsenic is listed as a known human carcinogen by IARC (Group 1), OSHA, NTP and EPA. In laboratory animal studies, chronic exposure to high concentrations of nickel has caused an increase in lung and nasal tumors. IARC has classified nickel as possibly carcinogenic to humans, group 2B.

## 12. ECOLOGICAL INFORMATION

### Environmental Effects:

PRODUCT: Product has not been tested for environmental properties. Lead shot has been shown to be toxic to aquatic species.

### COMPONENTS:

<u>Arsenic:</u>	<i>Daphnia magna</i> , 48 hr. LC <sub>50</sub> = 3.8 mg/L; Fathead minnow, 96 hr LC <sub>50</sub> = 9.9 mg/L
<u>Chromium:</u>	<i>Daphnia magna</i> , 48 hr. LC <sub>50</sub> = 0.022 mg/L; Fathead minnow, 96 hr LC <sub>50</sub> = 39 mg/L
<u>Copper:</u>	Copper concentrations from 0.1 to 1.0 mg/l have been found to be not toxic for most fish. However, concentrations of 0.015 to 3.0 mg/l have been reported as toxic, particularly in soft water to many kinds of fish, crustacea, mollusks, insects, and plankton.
<u>Lead:</u>	Bluegill sunfish, 48 hr. LC <sub>50</sub> = 2-5 mg/l. Lead is toxic to waterfowl.
<u>Nickel:</u>	Freshwater algae (4 species), 72 hr. EC <sub>50</sub> = 0.1 mg/L; <i>Daphnia magna</i> , 96 hr LC <sub>50</sub> = 0.51 mg/L; Rainbow trout, 96 hr LC <sub>50</sub> = 31.7 mg/L; Fathead minnow, 96 hr LC <sub>50</sub> = 3.1 mg/L
<u>Nitroglycerin:</u>	Bluegill sunfish, 96 hour LC <sub>50</sub> = 1.228 mg/l (static)
<u>Nitrocellulose:</u>	LC <sub>50</sub> > 1000 mg/l to fish, invertebrates, and algae.
<u>Zinc:</u>	The following concentrations of zinc have been reported as lethal to fish: 0.13 mg/l, for 12 – 24 hours to Rainbow trout fingerlings; 1.9 – 3.6 mg/l, 6 hr TLM (soft water, 30°C) to Bluegill Sunfish; 4 mg/l, 3 days (hard water) to Rainbow trout; 1 mg/l, 24 hours (soft water) to Sticklebacks. The presence of copper appears to have a synergistic effect on the toxicity of zinc towards fish.

### Environmental Fate:

MOBILITY:	Dissolved lead from degraded bullets may migrate through soil.
PERSISTENCE/DEGRADABILITY:	Not biodegradable. Bullets may fragment and decompose in soil leading to accumulation of lead.
BIOACCUMULATION:	No data

## 13. DISPOSAL CONSIDERATIONS

Care must be taken to prevent environmental contamination from the use of this material. The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding the treatment, storage and disposal for hazardous and nonhazardous wastes.

## 14. TRANSPORT INFORMATION

### Regulatory Information for US DOT, IATA, IMO, and ADR:

Proper Shipping Name: Cartridges, small arms (other than blanks)

Hazard Class Number and Description: Explosive 1.4S

<u>UN Identification Number:</u>	UN 0012
<u>Packing Group:</u>	PGII
<u>DOT Label(s) Required:</u>	Label Not Required for ground shipment.
<u>Marine Pollutant:</u>	None of the ingredients are classified by the DOT as a Marine Pollutant (as defined by 49 CFR 172.101, Appendix B)

**Additional Information:**

North American Emergency Response Guidebook Number: 114 Most Current Version is 2012

U.S. DEPARTMENT OF TRANSPORTATION SHIPPING REGULATIONS: This product is classified as dangerous goods under 49 CFR 172.101. Note: May be reclassified domestically as an ORM-D or Limited Quantity if packaged in accordance with 49 CFR 173.63.

TRANSPORT CANADA, TRANSPORTATION OF DANGEROUS GOODS REGULATIONS: This product is classified as Dangerous Goods (If packaged appropriately this product may ship as a Limited Quantity).

INTERNATIONAL AIR TRANSPORT ASSOCIATION (IATA): This product is classified as Dangerous Goods.

INTERNATIONAL MARITIME ORGANIZATION (IMO) DESIGNATION: This product is classified as Dangerous Goods (If packaged appropriately this product may ship as a Limited Quantity).

EUROPEAN AGREEMENT CONCERNING THE INTERNATIONAL CARRIAGE OF DANGEROUS GOODS BY ROAD (ADR): This product is classified by the United Nations Economic Commission for Europe to be dangerous goods. (If packaged appropriately this product may ship as a Limited Quantity).

**15. REGULATORY INFORMATION****US FEDERAL**

TSCA	The components of this product are listed on the Toxic Substance Control Act inventory.				
CERCLA:	Antimony, R.Q. = 5000 lbs.; Chromium, R.Q. = 5000 lbs.; Copper, R.Q.* = 5000 lbs.; Zinc, R.Q. = 1000 lbs.; Nickel, R.Q. = 100 lbs.; Lead, R.Q. = 10 lbs.; Nitroglycerin, R.Q. = 10 lbs; Dibutyl phthalate, R.Q. = 10 lbs.; Arsenic, R.Q. = 1 lb. (No reporting is required if diameter of the pieces of metal is equal to or exceeds 100 micrometers (0.004 inches)).				
SARA 313:	Copper, Lead and Lead compounds, Zinc (fume or dust), Nitroglycerin, Dibutyl phthalate, Nickel, Antimony, Chromium, Arsenic, Manganese				
SARA 311/312:	<u>Health:</u>	Acute – No Chronic - No	<u>Fire:</u> No	<u>Reactivity:</u> Yes	<u>Release of Pressure:</u> No
SARA 302 EHS List:	None of the components of this product are listed.				

\*RQ = Reportable Quantity

**STATE RIGHT-TO-KNOW STATUS**

Component	California	New Jersey	Pennsylvania	Massachusetts	Michigan
Copper	Not listed	X	X	X	X
Lead	X	X	X	X	X
Zinc	Not listed	X	Not listed	X	X
Nitrocellulose	Not listed	X	X	X	Not listed
Nitroglycerin	Not listed	X	X	X	Not listed
Dibutyl phthalate	Not listed	X	X	X	X
Nickel	X	X	X	X	X
Iron	Not listed	Not listed	Not listed	Not listed	Not listed
Antimony	Not listed	X	X	X	X
Tin	Not listed	Not listed	X	X	Not listed
Chromium (not hexavalent)	Not listed	X	X	X	X
Arsenic	X	X	X	X	X
Silicon	Not listed	Not listed	X	X	Not listed
Manganese	Not listed	X	X	X	Not listed

Bismuth	Not listed	Not listed	Not listed	Not listed	Not listed
Polyethylene	Not listed	Not listed	Not listed	Not listed	Not listed
Lead styphnate	X	Not listed	Not listed	X	Not listed

CALIFORNIA SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT (PROPOSITION 65)

Warning! This product contains detectable amounts of a chemical known to the State of California to cause cancer and/or birth defects or other reproductive harm.

GHS CLASSIFICATION

Explosive Division 1.4  
 STOT RE Category 1  
 Reproductive Toxicity Category 1A  
 Aquatic Environment, Chronic II

EUROPEAN REGULATIONS

All chemical components listed on EINECS except polyethylene and nitrocellulose (considered polymers)

Hazard Classification

Danger Symbols: E, T, N

Risk Phrases: R2, R48, R60, R63, R51/53

Safety Phrases: S2, S15, S20/21, S22, S39, S51, S61

German WGK Classification: Not know n.

CANADIAN REGULATIONS

DSL/NDSL Inventory: The components of this product are on the DSL

IDL: Lead, Antimony, Arsenic, Copper, Manganese, Nickel, Chromium, Tin, Dibutyl phthalate

CEPA PRIORITIES LIST: Dibutyl phthalate

WHMIS: This product is not subject to WHMIS. It is regulated as a Class 6 Explosive in Canada.

JAPANESE REGULATIONS

Existing National Inventory of Chemical Substances (ENCS): The components of this product are Listed

Japanese Priority Assessment Chemical Substances: None of the components of this product s are listed

OTHER INTERNATIONAL CHEMICAL INVENTORIES

Sw iss Giftliste List of Toxic Substances: All Components Listed

Australian Inventory (AICS): All Components Listed

**16. OTHER INFORMATION**

REVISIONS: 02

PREPARED BY: Olin Corporation

OTHER: Additional information available from: [www.winchester.com](http://www.winchester.com)

NOTICE: THE INFORMATION IN THIS SDS SHOULD BE PROVIDED TO ALL WHO WILL USE, HANDLE, STORE, TRANSPORT, OR OTHERWISE BE EXPOSED TO THIS PRODUCT. THIS INFORMATION HAS BEEN PREPARED FOR THE GUIDANCE OF PLANT ENGINEERING, OPERATIONS AND MANAGEMENT AND FOR PERSONS WORKING WITH OR HANDLING THIS PRODUCT. OLIN BELIEVES THIS INFORMATION TO BE RELIABLE AND CURRENT AS OF THE DATE OF PUBLICATION, BUT MAKES NO WARRANTY THAT IT IS.